


**Identification**

C<sub>3</sub>H<sub>6</sub>O  
 M = 58,08 g/mol  
 CAS [67-64-1]  
 EC number: 200-662-2  
 Taric code: 2914 11 00


**Synonyms**

Dimethyl ketone, 2-Propanone

**Applications**

solvents, analytical chemistry, synthesis of organic products, photography.



**Specifications**

assay (G.C.).....	min. 99,8 %	Suitable for highly volatile halogenated hydrocarbons trace analysis.
identity (IR-spectrum).....	passes test	ECD, from dichloromethane to 1,2,4-trichlorobenzene, no peaks are obtained greater than 1 ng/ml as tetrachloromethane.
density (20°/4°).....	0,787 - 0,791	
residue on evaporation.....	max. 0,0001 %	
water (K.F.).....	max. 0,2 %	

Suitable for organohalogenated pesticide and dioxins, furans and PCBs residue analysis.  
 ECD, from 1,2,4-trichlorobenzene to decachlorobiphenyl, no peaks are obtained greater than 3 pg/ml as lindane. No peaks are obtained in vicinity of 2,4,5-trichlorobiphenyl.

Suitable for pesticide and polycyclic aromatic hydrocarbons residue analysis.  
 FID, from 1-octanol to 1-tetradecanol, no peaks are obtained greater than 5 ng/ml as 1-tetradecanol. No peaks are obtained in vicinity of pyrene.

**Packaging**
**Packaging Code**

1 l  AC03091000  
 2,5 l  AC03092500

**Physical data**

- Density: 0,79 g/cm<sup>3</sup>
- Solub. in water: (20 °C): miscible
- Melting point: -95 °C
- Boiling point: 56 °C
- Flash point: < -20 °C
- Ignition temperature: 540 °C
- Vapour pressure: (20 °C) 233 hPa
- Refraction index: (n 20 °C/D) 1,3588
- Viscosity: (25 °C) 0,31 mPas
- Dipolar moment: (20 °C) 2,7 Debye
- Dielectric const.: (25 °C) 20,7
- Evap. heat: (56 °C) 521 KJ/kg
- Saturation conc.: (20 °C) 533 g/m<sup>3</sup>
- Expl. limit (upper): 13 Vol%
- Expl. limit (lower): 2,6 Vol%
- pH(395 g/l H<sub>2</sub>O, 20 °C) 5 - 6

**Safety - GHS**

**Signal Word:** Danger


**Hazard Statements:**

- H225: Highly flammable liquid and vapour.  
 H319: Causes serious eye irritation.  
 H336: May cause drowsiness or dizziness.  
 EUH066: Repeated exposure may cause skin dryness or cracking.

**Precautionary Statements:**

- P210: Keep away from heat / sparks / open flames / hot surfaces. - No smoking.  
 P241: Use explosion-proof electrical / ventilating / lighting / equipment.  
 P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P405: Store locked up.  
 P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

**Toxicological data**

- LD 50 (oral, rat): 5800 mg/kg
- MAK: 500 ml/m<sup>3</sup>, 1200 mg/m<sup>3</sup>
- WGK: 1
- Poison class CH (Swiss): 5

**Transport/storage**

- ADR: 3 F1 II • UN 1090 • ACETONE
- IMDG: 3 II • UN 1090 • ACETONE
- IATA/ICAO: 3 II • UN 1090 • ACETONE
- PAX: 305
- CAO: 307
- Store between 15°C and 25°C