

**Mixture T.B.N. : chlorobenzene/acetic acid, 2:1 v/v, according to ASTM D974, extra pure****Identification**

Taric code: 3814 00 90






**Applications**

analytical chemistry, in the petroleum industry.

**Specifications**

mixture according to:		iron (Fe).....	max. 0,00005 %
chlorobenzene.....	667 ml	lead (Pb).....	max. 0,00005 %
acetic acid (CH <sub>3</sub> COOH).....	333 ml	nickel (Ni).....	max. 0,00002 %
		zinc (Zn).....	max. 0,0005 %
sulfates (SO <sub>4</sub> ) .....	max. 0,0005 %	water (K.F.).....	max. 0,5 %

**Packaging****Packaging Code**

- 1 l  ME05131000
- 1 l  ME05131000
- 1 l  ME0513007E
- 1 l  ME0513007E
- 25 l  ME0513007E

**Physical data**• Density: 1,08 g/cm<sup>3</sup>**Safety - GHS**

Signal Word: Danger

**Hazard Statements:**

- H314: Causes severe skin burns and eye damage.
- H332: Harmful if inhaled.
- H411: Toxic to aquatic life with long lasting effects.
- EUH209A: Can become flammable in use.

**Precautionary Statements:**

- P260: Do not breathe dust / fume / gas / mist / vapours / spray.
- P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321: Specific treatment (see on this label).
- P405: Store locked up.
- P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

**Toxicological data**

- MAK: 10 ml/m<sup>3</sup>, 47 mg/m<sup>3</sup> (chlorobenzene);  
10 ml/m<sup>3</sup>, 25 mg/m<sup>3</sup> (acetic acid)
- Poison class CH (Swiss): 3

**Transport/storage**

- ADR: 8 C3 II • UN 3265 • CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Mixture T.B.N.)
- IMDG: 8 II • UN 3265 • CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Mixture T.B.N.)
- IATA/ICAO: 8 II • UN 3265 • CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Mixture T.B.N.)
- PAX: 808
- CAO: 812
- Store between 15°C and 25°C